

RX-1260CK / RX-2460CK

Feature

- 1.2 & 2.4GHz Band frequency receiving optional
- 8-Channel Option A/V Receiver Device
- Auto/Manual switcher & AV input feature
- Producing clear audio affect & stable video affect
- Being able to hook up to 8 cameras and sending signals simultaneously



Specification

Model Number	RX-1260CK	RX-2460CK
Frequency Band	1200MHz	2400MHz
Available Channel	8 Ch	8 Ch
Sub-Carrier Freq.	5.5 Mhz	6.5 Mhz
Operating Voltage	DC 12V	
Consumption Current	240 mA	
Video Output	75 Ohm Impedance, RCA x 2	
Audio Output	10k Ohm Impedance, RCA x 2	
Power Adaptor	12V / 500mA	
Type Standard	NTSC /PAL	
Weight (TX)	95 g	
Dimension (TX)	80x 63x 20 mm	
Antenna Connector	De-tacheable SMA connector	

*Specification & appearance may be subjected to change without notice

Standard Shipping Accessories

- SMA Standard Type Dipole Antenna*1
- Stereo Jack to RCA AV Output Cable*1

Order Model Number

RX-2460CK	2.4 GHz / 8CH Receiver /w standard shipping accessories
RX-1260CK	1.2 GHz / 8CH Receiver /w Standard shipping accessories
Each Item Shipping With Cable & Antenna	