

RF Bug Detector

Model No.: WR-2601



Function..

- Vibration detecting, Mute detecting, Beeping detecting, earphone detecting.
- It has display light which indicate strong or week signal. Interrupted no how and accurate completely.
- Broad detecting range (1MHz~6000MHz), no leak and miss.
- Can play down or adjust high detecting sensitivity (You can locate pinhole camera as long as the detecting range is dwindled and sensitivity is played down).
- No-voice vibration induction. As long as you put the device in your pocket, you can let it detect secretly in any special location.
- The signal of the RF Bug Detector is so different from pinhole camera's, so you can differentiate signal sort much easily.

Use..

- Detecting sort, as follows:
 1. Monitor. (1MHz—470MHz)
 2. Telephone monitor (50MHz—460MHz)
 3. Mobile phone monitor(500MHz—2500MHz)
 4. Digital monitor (900MHz—1900MHz)
 5. Car monitor (500MHz—1900MHz)
 6. Car tracker (900MHz—1900MHz)
 7. Pinhole camera (700MHz—5800MHz)
 8. Encrypt camera (2400MHz—5800MHz)
 9. Gambling fraudulent practices' device (130MHz—1900MHz)
 10. Wiring radiated source (4000MHz—6000MHz)
- Prevent such location as School, gymnasium, natatorium from spy with pinhole camera.
- It is applied to the lacionation which be forbidden using wireless equipment such as Hospital, Medical treatment centre, etc.
- No spy in military affairs or government department.
- Using this device, you can assist wireless surveillance system or wireless net route, net route mainframe to search no-interrupted and best incept location when they install these equipment.

Specification..

Frequency	1MHz ~6.0GHz
Alert mode 1	4 indicator lights and "DiDi" voice
Alert mode 2	Vibration + 4 indicator lights
Alert mod 3	No-voice, 4indicator lights and earphone detecting alert voice.
Button of adjusting sensitivity	Can play down or adjust high detecting sensitivity (You can locate pinhole camera as long as the detecting range is dwindled and sensitivity is played down).
Vibration induction	No-voice vibration induction. As long as you put the device in your pocket, you can let it detect secretly in any special location.
Work Voltage	3V
Work current	Alert:8mA Vibration:70mA
Battery	AAA/UM-4 dry cell x 2
Detecting distance	Detecting range:10cm-1000cm Subject to camera's transmission power. At power 50-100mw distance:50cm At power 200-400mw distance :150cm At power 500-700mw distance :500cm
Material	A B S + P C combination
Color	Bright silver white
Size	56 x 90 x 17 mm
Net weight	50 g
Size	155 x 130 x 42 mm(wrapping box)
Gross weight	190 g

Function Sketch map..






The mainframe will inform user about their detecting strong & week signal by the voice of "Ming"and number of Leds(green)



You can select he function button of "ON/OFF" and "Vibration/ Sensitivity" from the side of mainframe.

Complete set..

		
Detector x1	Earphone x1	Box x 1